Leica NA500 Series

Engineered for professionals by experts



your terms, on your site, Leica Geosystems and the Leica NA500 Series are your trusted partners for accurate measurements every time.

UNIQUE. FOCUSED. PROTECTED.

- Distinctive design and proven technology, inside and out
- Leica Geosystems understands construction and provides levels for all needs
- Expert knowledge and outstanding warranty you can count on - worldwide

KEY BENEFITS

- Quick and easy measurements
- Unique design and highest quality of results for levelling needs
- Manufactured for the most rugged sites and the harshest conditions
- Expert knowledge of Leica Geosystems with more than 270 service centres worldwide
- Top-notch warranty





Leica NA500 Series







Leica NA520

Leica NA524

Leica NA532

TECHNICAL DATA			
Standard deviation for 1 km double levelling (ISO17123-2)	2.5 mm	1.9 mm	1.6 mm
TELESCOPE			
Telescope image		Upright	
Magnification	20 x	24 x	32 x
Objective aperture		36 mm	
Shortest target distance from instr. axis		<1.0 m	
Field of view at 100 m		<2.1 m	
Multiplication factor		100	
Additive constant		0	
COMPENSATOR			
Working range		± 15′	
Setting accuracy (standard deviation)		<0.5"	
Sensitivity		8'/2 mm	
HORIZONTAL CIRCLE			
Graduation		360°	
Graduation interval		1°	



Operating temperature range

Weight (net)

Protection

PROTECT is subject to Leica Geosystems' international manufacturer warranty and the general terms and conditions for PROTECT. For more information visit www.leica-geosystems.com/protect

Leica Geosystems offers a wide variety of construction instruments for your everyday use. Contact your local Leica Geosystems dealer for more information on our solutions.







1.5 kg

-20° C to +50° C

IP56



Digital Levels

Construction Lasers

Pipe Lasers

Cable Locators

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland - Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2016. 843050en - 01.16 - INT

